

Description

LED Retrofit Module

Technical Specifications

LED power (W)	15W
Mounting: Recessed Ceiling	different rings
Lumen output (Lm)	100Lm/W
Beam angle (°)	60°
CCT(K°)	3000K° or 4000K°
IK rating	IK03
IP factor	IP20
CRI	RA>90
Rate Inpute (Vac)	220-230V 50Hz
Flicker free	Anti Glare UGR<19
Power factor	>0,95
LED chip	COB
Energieklasse	F
Alum. Housing	white
Working temp.	-40° / +50°
Warranty (years)	3
Dimmable driver incl.	Triac dim or 0-10V dim
Dimensions Øx h (mm)	50x75,5mm
Long lifespan	50000Hrs
Applications in office, supermarket, shop, school, hotel	

02/2022



Also available in:

- LED Module 15W Triac Dim. 3000K°
- LED Module 15W Triac Dim. 4000K°
- LED Module 15W 0-10V Dim. 3000K°
- LED Module 15W 0-10V Dim. 4000K°
- LED Module 15W PWM Dim. TW

Artikel No.


- 0253-015-3000
- 0253-015-4000
- 0254-015-3000
- 0254-015-4000
- 0255-015-TW

(2200K°....3000K°)

15W	Anti glare	UGR<19	CE
Powered by tuya Intelligence Inside	IP20	DIM	RoHS



One module, different mounting rings



Durable – Delightfull – LED

